



PM-60Vet Pulse Oximeter

- High resolution 2.4" color LCD display
- Two selectable working modes: spot check and continuous monitoring
- Adjustable audible and visual alarms
- Real time data transfer by infrared technology
- Batteries to support up to 36 hours continuous working
- Protective cover and carrying case perfect for portable monitoring needs



PM-60Vet

Pulse Oximeter

Technical Specifications

Safety

Meet the requirements of IEC60601 series,
CE marking according to MDD93/42/EEC

Type of Protection Class II with internal electric power supply
Degree of Protection BF (defibrillation proof)
Protection Against Ingress of Liquid's: IPX2

Dimension and Weight

Dimension 55(W)X120(H)X30(D)mm
2.1"X4.7"X1.2"
Weight Maximum weight 300g
(With battery) / 0.66lb

Operation Environment

Temperature 0~40°C/32~104°F
Humidity 15~95%(non-condensing)

Storage Environment

Temperature -20°C ~ +60°C / -4~140°F
Humidity 10% ~ 95%
(Non-condensing)

Performance Specifications

Display 2.4" color TFT
Resolution 320×240
Multi displays selectable Standard screen display
Waveform display
Trace 1 plethysmogram waveform
Indicator Alarm indicator light
Power indicator light
Pulse tone
Alarm sound
Button tones
Interface One dual-purpose socket for
connecting SpO₂ sensor and
communication cable.
IR interface Infrared link allows downloading
realtime patient data to computer
DC Power interface Charger stand for Li-ion battery
DC Power Requirements Input voltage 5V DC
Power 1.2A

Battery *Li-ion Battery*
2 hours for charging;24 hours for
continuous working
AA batteries
(for 3 pieces)36 hours for
continuous working
Trend memory *Monitoring mode*
Resolution: 2s
Maximum time: 96h
Spot-Check mode
Review of up to 4,000 data;
measure up to 99 patients
Alarm User-adjustable High and Low limits
3-level audible and visual alarm

SpO₂

Measurement range 0~100%
Resolution 1%
Accuracy ±2%(70~100%,Adult/Pediatric,
non-motion)
±3%(70~100%,Neonate, non-motion)
±3%(70~100%,Adult/Pediatric/
Neonate,motion)
0~69% unspecified
Alarm range 50~100%
Refreshing rate 1 s
Averaging time 7 s (Sensitivity set HIGH)
9 s (Sensitivity set MED)
11 s (Sensitivity set LOW)

Pulse Rate

Range 18~300bpm
Resolution 1bpm
Accuracy ±3bpm(non-motion)
±5bpm(motion)
Alarm range 18~300bpm
Refreshing rate 1 s
Averaging time 7 s (Sensitivity set HIGH)
9 s (Sensitivity set MED)
11 s (Sensitivity set LOW)

Order Information

Part Number	Description
0852B-02000	Main unit (with standard reusable sensor)
0852-10-77701	Carrying case
0852-21-77412-53	Protective cover
0852-30-77503	Battery charging kit (Euro)
0852-30-77504	Battery charging kit (US)
0852-30-77505	Battery charging kit (UK)
0852-30-77531	Pole mounting kit
0852-30-77491	Data management kit

Partial list of choices, for more details please refer to the price list.



Protective Cover



Charger Stand



MINDRAY™

Mindray Building, Keji 12th Road South, High-tech Industrial Park,
Nanshan, Shenzhen 518057, P. R. China

Tel: +86 755 26582492, 26582888 Fax: +86 755 26582680
E-mail: intl-market@mindray.com Website: www.mindray.com



USA Corporate Office

8650 154th Ave., NE Redmond, WA 98052
Tel: 425-881-0361 Fax: 425-881-0879
E-mail: usa@mindray.com
Toll free: 888-816-8188 ; 800-656-9088